

Open-WBO @ MaxSAT 2018

Ruben Martins
rubenm@cs.cmu.edu
CMU, USA

Norbert Manthey
nmanthey@conp-solutions.com
Dresden, Germany

Miguel Terra-Neves, Vasco Manquinho, Inês Lynce
{neves,vmm,ines}@inesc-id.pt
INESC-ID/IST, Portugal

I. INTRODUCTION

Open-WBO [1] is an open source MaxSAT solver that supports several MaxSAT algorithms [2], [3], [4], [5], [6], [7], [8] and MaxSAT solvers [9], [10]. Open-WBO is particularly efficient for unweighted MaxSAT and has been one of the best solvers in the MaxSAT Evaluations from 2014 to 2017. Two versions of Open-WBO were submitted to the MaxSAT Evaluation 2018 (MSE2018): OPEN-WBO-RISS and OPEN-WBO-GLUC. The remainder of this document describes the MaxSAT algorithms and SAT solvers used in each version.

II. SAT SOLVERS

OPEN-WBO is based on the data structures of MINISAT 2.2 [9], [11]. Therefore, solvers based on MINISAT 2.2 can be used as potential backend, including formula simplification. The default SAT backend is GLUCOSE 4.1 [10], [12], which has been improved for incremental search [13]. Furthermore, formula simplification is typically disabled, as most work on incremental SAT solving with formula simplification, e.g. [14], has not been backported into MINISAT 2.2 or GLUCOSE 4.1.

Besides GLUCOSE 4.1, OPEN-WBO now supports MINISAT 2.2 and RISS [15], where MINISAT 2.2 [9] is the latest version from GitHub [11]. In this version, some data structures are different, for example the representation of the conflicting set of assumption literals. Also, the file structure changed. Both RISS and MINISAT 2.2 support reserving variables when a SAT solver is created, which allows to store them in a more compact way. Given the variety of solvers and features, we adapted OPEN-WBO to support solvers with both the old as well as the new file structure, and furthermore, allow to select whether the variable reservation feature is available during compile time. The different versions submitted to the MaxSAT Evaluation 2018 differ between themselves on the backend SAT solver. Namely, OPEN-WBO-RISS and OPEN-WBO-GLUC use RISS and GLUCOSE 4.1, respectively.

III. MAXSAT ALGORITHMS

In this section we briefly describe the algorithms used for the complete and incomplete tracks at the MSE2018.

A. Complete Track

For the complete track, OPEN-WBO uses a variant of the unsatisfiability-based algorithm MSU3 [3] for unweighted problems and the OLL algorithm [7] for weighted instances. These algorithms work by iteratively refining a lower bound

λ on the number of unsatisfied soft clauses until an optimum solution is found. Both MSU3 and OLL use the Totalizer encoding for incremental MaxSAT solving [4]. For unweighted MaxSAT, we extended the incremental MSU3 algorithm [4] with resolution-based partitioning techniques [8]. We represent a MaxSAT formula using a resolution-based graph representation and iteratively join partitions by using a proximity measure extracted from the graph representation of the formula. The algorithm ends when only one partition remains and the optimal solution is found. Since the partitioning of some MaxSAT formulas may be unfeasible or not significant, we heuristically choose to run MSU3 with or without partitions. In particular, we do not use partition-based techniques when one of the following criteria is met: (i) the formula is too large ($> 1,000,000$ clauses), (ii) the ratio between the number of partitions and soft clauses is too high (> 0.8), or (iii) the sparsity of the graph is too small (< 0.04). For weighted MaxSAT, we use the OLL algorithm [7] without further improvements.

B. Incomplete Track

For the incomplete track, OPEN-WBO uses a linear search algorithm SAT-UNSAT [16] with lexicographical optimization for weighted problems [17]. This algorithm works by performing a sequence of calls to a SAT solver and refining an upper bound μ on the number of unsatisfied soft clauses. To restrict μ at each iteration, we need to encode a cardinality constraint (pseudo-Boolean constraint) for unweighted (weighted) problems into CNF. The LSU version uses the Modulo Totalizer encoding [18] for cardinality constraints and the Adder [19] or Generalized Totalizer encoding (GTE) [20] for pseudo-Boolean constraints.

Relatively to the MSE17 version, we did the following improvements: (i) we incorporated solution-based phase saving [21], [22], and (ii) for weighted problems, we dynamically choose between the Adder encoding and the GTE encoding. We choose the former when the number of auxiliary clauses created by the GTE encoding exceeds 3,000,000.

IV. AVAILABILITY

The latest release of Open-WBO is available under a MIT license in GitHub at <https://github.com/sat-group/open-wbo>. To contact the authors please send an email to: open-wbo@sat.inesc-id.pt.

ACKNOWLEDGMENTS

We would like to thank Laurent Simon and Gilles Audemard for allowing us to use GLUCOSE 4.1 in the MaxSAT Evaluation. We would also like to thank Niklas Eén and Niklas Sörensson for the development of MINISAT 2.2. We would also like to thank all the collaborators on previous versions of OPEN-WBO, namely Saurabh Joshi and Mikoláš Janota.

REFERENCES

- [1] R. Martins, V. Manquinho, and I. Lynce, “Open-WBO: a Modular MaxSAT Solver,” in *SAT*, ser. LNCS, vol. 8561. Springer, 2014, pp. 438–445.
- [2] V. Manquinho, J. Marques-Silva, and J. Planes, “Algorithms for Weighted Boolean Optimization,” in *SAT*. Springer, 2009, pp. 495–508.
- [3] J. Marques-Silva and J. Planes, “On Using Unsatisfiability for Solving Maximum Satisfiability,” *CoRR*, 2007.
- [4] R. Martins, S. Joshi, V. Manquinho, and I. Lynce, “Incremental Cardinality Constraints for MaxSAT,” in *CP*. Springer, 2014, pp. 531–548.
- [5] R. Martins, V. Manquinho, and I. Lynce, “On Partitioning for Maximum Satisfiability,” in *ECAI*. IOS Press, 2012, pp. 913–914.
- [6] R. Martins, V. M. Manquinho, and I. Lynce, “Community-based partitioning for maxsat solving,” in *SAT*. Springer, 2013, pp. 182–191.
- [7] A. Morgado, C. Dodaro, and J. Marques-Silva, “Core-Guided MaxSAT with Soft Cardinality Constraints,” in *CP*. Springer, 2014, pp. 564–573.
- [8] M. Neves, R. Martins, M. Janota, I. Lynce, and V. M. Manquinho, “Exploiting Resolution-Based Representations for MaxSAT Solving,” in *SAT*. Springer, 2015, pp. 272–286.
- [9] N. Eén and N. Sörensson, “An Extensible SAT-solver,” in *SAT*. Springer, 2003, pp. 502–518.
- [10] G. Audemard and L. Simon, “Predicting Learnt Clauses Quality in Modern SAT Solvers,” in *IJCAI*, 2009, pp. 399–404.
- [11] N. Sörensson, N. Een, and N. Manthey. (2018, May) GitHub repository for MiniSat. <https://github.com/conp-solutions/minisat>.
- [12] G. Audemard and L. Simon. (2018, May) Glucose’s home page. <http://www.labri.fr/perso/lsimon/glucose>.
- [13] G. Audemard, J.-M. Lagniez, and L. Simon, “Improving glucose for incremental sat solving with assumptions: Application to mus extraction,” in *SAT*. Springer, 2013.
- [14] A. Nadel, V. Ryvchin, and O. Strichman, “Ultimately incremental sat,” in *SAT*, C. Sinz and U. Egly, Eds. Springer, 2014.
- [15] N. Manthey. (2018, May) GitHub repository for Riss. <https://github.com/conp-solutions/riss>.
- [16] D. Le Berre and A. Parrain, “The Sat4j library, release 2.2,” *Journal on Satisfiability, Boolean Modeling and Computation*, vol. 7, no. 2-3, pp. 59–6, 2010.
- [17] J. Marques-Silva, J. Argelich, A. Graça, and I. Lynce, “Boolean lexicographic optimization: algorithms & applications,” *Annals of Mathematics and Artificial Intelligence*, vol. 62, no. 3-4, pp. 317–343, 2011.
- [18] T. Ogawa, Y. Liu, R. Hasegawa, M. Koshimura, and H. Fujita, “Modulo Based CNF Encoding of Cardinality Constraints and Its Application to MaxSAT Solvers,” in *ICTAI*. IEEE, 2013, pp. 9 – 17.
- [19] J. P. Warners, “A Linear-Time Transformation of Linear Inequalities into Conjunctive Normal Form,” *Information Processing Letters*, vol. 68, no. 2, pp. 63–69, 1998.
- [20] S. Joshi, R. Martins, and V. M. Manquinho, “Generalized Totalizer Encoding for Pseudo-Boolean Constraints,” in *CP*. Springer, 2015, pp. 200–209.
- [21] C. Ansótegui and J. Gabàs, “WPM3: An (in)complete algorithm for weighted partial MaxSAT,” *Artificial Intelligence*, vol. 250, pp. 37–57, 2017.
- [22] E. Demirović and P. J. Stuckey, “Local-Style Search in the Linear MaxSAT Algorithm: A Computational Study of Solution-Based Phase Saving,” in *Pragmatics of SAT Workshop*, 2018.