

QMAXSAT in MaxSAT Evaluation 2018

Aolong Zha

Faculty of Information Science and Electrical Engineering
Kyushu University

744 Motooka, Nishi-ku, Fukuoka, Japan
cyouryuuryuu@gmail.com

QMAXSAT is a satisfiability-based solver, which uses CNF encoding of pseudo-Boolean (PB) constraints [1]. The efficiency of MaxSAT solvers depends on critically on which SAT solver we use and how we encode the PB constraints. The QMAXSAT is obtained by adapting a CDCL based SAT solver GLUCOSE 3.0 [2], [3]. In addition, we introduce a new encoding method, called n -level modulo totalizer encoding in to our solver. This encoding is a hybrid between Modulo Totalizer (MTO) [4] and Weighted Totalizer (WTO) [5], incorporating the idea of mixed radix base [6].

Let $\phi = \{(C_1, w_1), \dots, (C_m, w_m), C_{m+1}, \dots, C_{m+m'}\}$ be a MaxSAT [7] instance where C_i is a soft clause with weight w_i ($i = 1, \dots, m$) and C_{m+j} is a hard clause ($j = 1, \dots, m'$). We added a new blocking variable, b_i , to each soft clause C_i ($i = 1, \dots, m$). Solving the MaxSAT problem for ϕ is reduced to finding a SAT model of $\phi' = \{C_1 \vee b_1, \dots, C_m \vee b_m, C_{m+1}, \dots, C_{m+m'}\}$, which minimizes $\sum_{i=1}^m w_i b_i$.

Such SAT models are obtained using a SAT solver as follows: Run the SAT solver to get an initial model and calculate $k = \sum_i w_i b_i$ in it, add PB constraint $\sum_i w_i b_i < k$, and run the solver again. If ϕ' is unsatisfiable, then ϕ is also unsatisfiable as the MaxSAT problem. Otherwise, the process is repeated with the new smaller solution. The latest model is a MaxSAT solution of ϕ . QMAXSAT leaves the manipulation of the PB constraints to GLUCOSE by encoding them into SAT.

We introduce a hybrid encoding [8] which inherits modular arithmetic from MTO and distinct combinations of weights from WTO. The latter is essentially the same as Generalized Totalizer, which only generate auxiliary variables for each unique combination of weights. We also enhanced the encoding by multi-level modulo arithmetic based on a mixed radix numeral system [9]. This encoding method always produces a polynomial-size CNF in the number of input variables.

It is important to find a suitable mixed radix base with low time-consumption that reduces the number of auxiliary variables for our new encoding. We select the integer whose rate of divisibility is the highest for all weights¹ as the suitable modulus for each digit. Furthermore, we also add other heuristics tailored in our implementation, such as evaluating and voting for the candidates of modulus, dynamically adjusting the lower limit of the required rate of divisibility, etc.

¹Before selecting the next modulus, we update all the weights to their quotients of dividing the previous selected modulus.

REFERENCES

- [1] M. Koshimura, T. Zhang, H. Fujita, and R. Hasegawa, "QMaxSAT: A Partial Max-SAT Solver," *JSAT*, vol. 8, no. 1/2, pp. 95–100, 2012.
- [2] G. Audemard and L. Simon, "Predicting Learnt Clauses Quality in Modern SAT Solvers," in *IJCAI 2009, Proceedings of the 21st International Joint Conference on Artificial Intelligence, Pasadena, California, USA, July 11-17, 2009*, C. Boutilier, Ed., 2009, pp. 399–404.
- [3] N. Eén and N. Sörensson, "An Extensible SAT-solver," in *Theory and Applications of Satisfiability Testing*, E. Giunchiglia and A. Tacchella, Eds. Berlin, Heidelberg: Springer Berlin Heidelberg, 2004, pp. 502–518.
- [4] T. Ogawa, Y. Liu, R. Hasegawa, M. Koshimura, and H. Fujita, "Modulo Based CNF Encoding of Cardinality Constraints and Its Application to MaxSAT Solvers," in *2013 IEEE 25th International Conference on Tools with Artificial Intelligence, Herndon, VA, USA, November 4-6, 2013*. IEEE Computer Society, 2013, pp. 9–17.
- [5] S. Hayata and R. Hasegawa, "Improvement in CNF Encoding of Cardinality Constraints for Weighted Partial MaxSAT," *SIG-FPAI, in Japanese*, vol. 4, no. 04, pp. 85–90, 2015.
- [6] M. Codish, Y. Fekete, C. Fuhs, and P. Schneider-Kamp, "Optimal Base Encodings for Pseudo-Boolean Constraints," in *Tools and Algorithms for the Construction and Analysis of Systems - 17th International Conference, TACAS 2011, Held as Part of the Joint European Conferences on Theory and Practice of Software, ETAPS 2011, Saarbrücken, Germany, March 26-April 3, 2011. Proceedings*, ser. Lecture Notes in Computer Science, P. A. Abdulla and K. R. M. Leino, Eds., vol. 6605. Springer, 2011, pp. 189–204.
- [7] C. M. Li and F. Manyà, "MaxSAT, Hard and Soft Constraints," in *Handbook of Satisfiability*, ser. Frontiers in Artificial Intelligence and Applications, A. Biere, M. Heule, H. van Maaren, and T. Walsh, Eds. IOS Press, 2009, vol. 185, pp. 613–631.
- [8] A. Zha, M. Koshimura, and H. Fujita, "A Hybrid Encoding of Pseudo-Boolean Constraints into CNF," in *Conference on Technologies and Applications of Artificial Intelligence, TAAI 2017, Taipei, Taiwan, December 1-3, 2017*. IEEE, 2017, pp. 9–12.
- [9] A. Zha, N. Uemura, M. Koshimura, and H. Fujita, "Mixed Radix Weight Totalizer Encoding for Pseudo-Boolean Constraints," in *2017 IEEE 29th International Conference on Tools with Artificial Intelligence, Boston, MA, USA, November 6-8, 2017*. IEEE Computer Society, 2017, pp. 868–875.